







ST800-DI16SC-C2 8.00Pitch



Technical data

Connection data	
Connection to PLC	HE 10 connectors 20-pin
Connection type (field)	Screw bolt up
Connection size (field)	0.34 ~ 2.5mm ² (AWG22 ~ 14)

Input-output data	
Operating voltage	24VDC ± 10%
Max. current for channel	1.5A
Number of signals	16
PLC card supply voltage / LED voltage status	24VDC ± 10% / LED green
LED fuse indication per channel	-
PLC card supply current	2A
Fuse per channel	-

General data	
Ambient temperature	-25°C ~ 50°C
Storage temperature	-40°C ~ 60°C
Rated voltage	≤ 50V AC
Insulation test voltage	0.5KV DC
Weight 6.50 / 8.00	Approx. ---g / 308.6g

Dimensions	
Length x width x height (mm)	6.50 Pitch -
	8.00 Pitch 165 x 87.5 x 73.3

Mounting rail	TS35 (Weidmuller)
---------------	-------------------

Ordering data

Order No.	
--- (6.50 Pitch)	822220010 (8.00 Pitch)

Accessories / Spare part

Terminal markers	6.50 8.00 DEK 5/8
Cross-connector	6.50 8.00 COM-8009

Use with

Front connector	Cable
S7-300S-DA20P	DAHHC20-10K24B